

A350 PRO

Color Screen Time & Attendance



8ти

((...))







WI Pro is the new generation fingerprint time attendance terminal based on Linux platform and supports cloud application. W1 Pro houses 2.8-inches color LCD and full capacitive touch keypads along with touch optical fingerprint sensor Full upgrade for W series with battery will power your business anytime and anywhere. The webserver function realizes the easily self management of the device



Cloud based fingerprint and RFID time attendance device

Features

1Ghz Linux Based CPU

The new Linux based 1Ghz processor ensures the 1:3000 comparison time less than 0.5 second



Optional WIFI & Bluetooth

The WiFi & Bluetooth function ensures power on to work, and realize the flexible installation of the device.



Optional 4G

The 4G commnication ensures the flexible communication saving the installation cost and applied in the area with poor or without internet.



Optional Battery

The long life battery ensuring up to 10 hours portable application.



Touch Active Fingerprint Sensor

The touch active sensor ensures the quick response for each detection and saving the total power consumption of the device.



Touch Active Keypad

The touch active sensor ensures the best user experiences for and saving the total power consumption of the device.



Colorful LCD Screen

The Colorful LCD screen ensures the best interaction and user experiences and can also provide clear notifications to the users.



Webserver

The Webserver ensures the easily quick connection and self management of the device $\,$




Cloud application

The web based cloud application let you access to the device by any mobile terminal from anytime and anywhere.

Key Specifications

User	3000
Card	3000
Record	100,000
Communication	RS232, Mini USB & USB Host, TCP/IP,Optional WiFi/Bluetooth/4G
Identification mode	finger, password, card (optional EM and Mifare)
Identification speed	<0.5s
Card reading distance	1~5cm (125KHz), 13.56MHz >2CM) for standard CR80 card
WebServer	Support
CPU	Linux 1G
RFID card	Standard EM and Optional Mifare
Working Temperature	-30°C~60°C
Humidity	20% to 90%
Power	DC12V
Battery	Optional

System configurations





Anviz Global Inc.

41656 Christy Street Fremont , Fremont , CA,94538
Tel: 408-2637700 | Toll-free:1-855-268-4948 | Inquiry: sales@anviz.com | www.anviz.com

©2019 Anviz Gloabl Inc. Anviz and identifying product names and numbers herein are registered trademarks of Anviz Global Inc. All non-Anviz brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.

Due to the consistent improvement of the product, this specification and appearance are subject to change without notice.